

Large Commercial Fan Heaters - Wireless Controlled

Larger, more powerful commercial fan heaters providing a "heat throw" of 11m at maximum fan speed. The intelligent fan control optimises fan speed and heat output to quickly achieve and control a comfort temperature whilst maintaining a very low noise level. Airflow temperature depends on rating of fan heaters. Ideal for large areas such as warehouses, factories, large workshops and many other commercial applications.

- 9kW, 12kW or 15kW rating
- 3 phase supply
- Sensor to detect the room temperature and heat output
- Intelligent Fan Control feature:- The fan speed of the heater automatically adjusts relative to the room's current temperature in order to achieve warm airflow temperature. This eliminates the heater from blowing cold air when initially powered on in a cold room.
- Incorporates EC motor for improved energy efficiency
- Safety monitoring feature to identify overheating, fan failure and certain electronic faults
- Wireless controlled by separately purchased CRXSL controller
- One CRXSL controller can operate multiple RX heaters
- Time/Manual mode in CRXSL controller:
 - Allows fan and heat settings to be adjusted manually
 - Allows set time schedule for fan and heat settings
- CRXSL controller is compatible with separately purchased MRX1 Multizone controller for 'zoning' of the heating system
- Instant directional warmth
- 2 automatic fan speeds, 3 heat settings
- Fan only setting for air circulation
- Wall mounted with multi-directional brackets supplied (180° horizontal, 45° vertical)
- Maximum heat throw – 11 metres
- Finished in white/grey



Dimensions (mm) & Weight (kg):

Height (mm)	Depth (mm)	Width (mm)	Weight (kg)	Max. dBA
300	390	360	14	59

Model No.	Rating (kW)	Optimum Mounting Height (m)	3 Phase
CH09iRX	9	2.5-4	●
CH12iRX	12	2.5-4	●
CH15iRX	15	2.5-4	●

CRXSL Energy Saving Features

- 6 temperature programmes per day
- 7-day heating programmes per week
- Maintains temperature within 0.5°C
- Set temperature in 0.5 degrees increments
- Reduced power consumption in standby mode



Model No.	Rating (kW)	Automatic Fan Speeds*	Heat Settings
CH09iRX	9	2	3
CH12iRX	12	2	3
CH15iRX	15	2	3

* Only available in manual mode